

This document describes the configurations of User Access and Authentication Configuration, including AAA, NAC, Policy Association, and Kerberos Snooping.

Two terminal type identification methods are available: A switch identifies terminal types by analyzing MAC addresses, DHCP option information, and user agent (UA) information of terminals and then ...

```
// Set port GE0/0/1 link type to trunk and allow VLAN 10 and 20. // Set port GE0/0/4 link type to access and use VLAN 10 as default VLAN. // Do factory recovery in user-view. // Check latest factory ...
```

An access port belongs to and carries the traffic of only one VLAN within 2-layer switch. Traffic is both received and sent in native formats with no VLAN tagging whatsoever.

The real question for anyone serious about their network's performance, reliability, and security isn't if they need these commands, but how deeply they understand and utilize the nuances ...

1. access: Mainly used to access terminal devices, such as PCs, servers, print servers, etc. 2. trunk: Mainly used to connect to other switches to carry multiple VLANs on the line.

The document provides configuration instructions and commands for basic switch configuration using Huawei switches. It covers topics such as changing the hostname, configuring user accounts and ...

This text is a guide detailing Basic Command Line Interface (CLI) Commands on Huawei brand switches. It provides step-by-step instructions for users to perform fundamental network configuration ...

The terminal access allows Ethernet access using LAN switches, WLAN access using APs, and asymmetric digital subscriber line (ADSL) access using digital subscriber line access multiplexers ...

Access the switch console or CLI: Connect to the switch console using a terminal emulator or access the switch CLI remotely through SSH or Telnet. Enter privilege mode: If you're ...

Web: <https://www.busydoniemiecwaldii.pl>